

RIGID VINYL CLICK

WIDTH: 9"

LENGTH: 59"

THICKNESS: 5.5MM

WEAR LAYER: 20MIL (.5MM)

FINISH: SURFACE GUARDIAN PRO

**WARRANTY: LIMITED LIFETIME STRUCTURAL
& RESIDENTIAL FINISH**



CANTERBURY OAK



BRAIR OAK



GHENT OAK



NIGHTCASTLE OAK



CHARLEMAGNE OAK



CAMARILLA OAK



DURHAM OAK



KINGSGUARD OAK



KNIGHT OAK



CLYDE MAPLE



CHANCELLOR OAK



ADMIRAL OAK



GRIFFITH OAK



GALLOWAY HICKORY



FALCONER OAK



ROHAN OAK

Benefits

Finish:	Commercially Rated Wear Layer 100% Renewable with Warranty Intact Lifetime Finish Warranty
Structure:	Higher Stability & Density 100% Quality Virgin Vinyl Purcore Rigid Plus - Lifetime Structure Warranty
Clean Air:	Formaldehyde Free Ortho Phthalate Free 100% Floor Score Certified

Features

Dimensions:	9" x 59" x 5.5mm
Wear Layer:	20mil (.5mm)
Surface Texture:	Various
Finish:	Surface Guardian Pro®
Install:	Float (Click Lock System)
Edge Detail:	4 Sided Painted Bevel
Certified:	FloorScore®
Usage:	Residential, Commercial
Warranty:	Limited Lifetime Residential finish Limited Lifetime Residential structural 10 year commercial finish 20 year commercial structural

> Surface Guardian Pro Protection

- EIR Wood Texture
- UV Ceramic Bead
- Stain Resistant



< Printed Top Layer

- Low Sheen
- High Definition
- Real Wood Visuals

> IXPE Acoustic Pad

- Sound Reduction
- Feet & Back Support
- Waterproof & Hypoallergenic

< Purecore Rigid Construction

- Virgin Vinyl & 60% Stone
- 3 Season Room Compatible
- Formaldehyde & Phthalate Free

ASTM

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass (PSI Equivalent > 5,500+ lbs.)	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected * E1 Rating	EN 7171-1
Impact Insulation Class IIC	Eternity Underlayment IIC 71 Delta 21	ASTM E492, E-989
ISO 14001 Certified Environmental Management System		



Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3

