



Oceanside Oak



■ Cadiz Oak EDCAD6O3MM



■ Barcelona Spruce EDBAR6S3MM



■ Granada Walnut EDGRA6W3MM



■ Tortosa Sisal EDTOR6S3MM



■ Madrid Maple EDMAD6M3MM



■ Valencia Teak EDVAL6T3MM



■ Caceres Acacia EDCAC6A3MM



■ Montecito Oak SMMON7O3MM



■ Redondo Oak SMRED7O3MM



■ Piedmont Oak SMPIE7O3MM



■ Riata Hickory SMRIA7H3MM



■ Oceanside Oak SMOCE7O3MM



■ Bridle Hickory SMBRI7H3MM



■ Terret Walnut SMTER7W3MM



■ Pelham Maple SMPEL7M3MM

Features

- Length: 48"
- Width: ■ 6"
■ 7.25"
- Thickness: 3mm
20mil wear layer
- Finish: Surface Guardian Pro UV Coating
- Edge Detail: Microbevel
- FloorScore® Certified: Registration # SCS-FS-03695
- Warranty: Lifetime Residential Finish & Lifetime Residential Structure
20 year Commercial Structural & 10 year Commercial Finish
- Maintenance: Clean with TrueClean Floor Cleaner.
For full care and maintenance instructions visit
HallmarkFloors.com/Floor-Care-Maintenance

Benefits

- Fashion: Natural Low Sheen
Embossed Wood Texture
Fashionable Widths & Longer Lengths
- Performance: Waterproof
Anti Bacterial & Fungal Control
100% Renewable with Hallmark's ABC Recoat System
PureCore Ultra- 100% Pure Virgin Vinyl
- Clean Air: Formaldehyde Free & Ortho Phthalate Free
Safer Indoor Environment for Children
100% FloorScore Certified



Trim Options

- Multipurpose Reducer
- T-molding
- Flush Stair Nosing

Installation



Glue Down

Double Glue with Eternity LVT underlayment system or equivalent.



ASTM Testing

| | | |
|--|----------------|---------------|
| Flexibility | Pass | ASTM F137 |
| Thickness Standard | Pass | ASTM F386 |
| Resistance to Chemicals (5 min.) | Pass | ASTM F925 5 |
| Resistance to Chemicals (24 hr.) | Pass | ASTM F925 |
| Stain Resistance | Pass | ASTM F925 |
| Heat Stability by Color Change | Pass | ASTM F1514 |
| Light Stability by Color Change | Pass | ASTM F1515 |
| Dimensional Stability after exposure to heat | Pass | ASTM F2199 |
| Fire Resistance | Class C - Pass | ASTM E 648 |
| Coefficient of Friction | Pass | ASTM D2047-04 |
| Static Load | Pass | ASTM F970-07 |
| Stain Resistance | Pass | ASTM F925 |
| Short Term Indentation | Pass | ASTM F1914-98 |
| Smoke Density | Pass | ASTM E662-09 |
| Wear Resistance | High | ASTM F510-93 |
| Formaldehyde Emission (air) | None Detected | EN 7171-1 |

ISO 14001 Certified Environmental Management System



Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring. Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3