

# Total Floor Care

## Hardwood Floor Touch-Up



# Hallmark Floors – Mohawk Finishes Touch Up Kit

## Kit Contents



- Ultra Bond Waterborne Clear Finish Marker: One sponge tip marker.
- Felt Tip Marker/Markers: One or two felt tipped color markers. The markers will be either Ultra Mark 2000 or Pro Mark II. Number of markers and type will be determined by the color of the floor.
- Fill Stick/Sticks: One or two Fil-Stik, color fill sticks.

## 1. Mohawk Finishes - Ultra™ Bond Waterborne Clear Finish Marker

Surface Scratches – Skill Level

Basic

Start with Ultra Bond Waterborne Clear Finish Marker to touch up the scratch.

Product Description: Mohawk Ultra™ Bond Waterborne Clear Finish Marker produces a durable, chemical resistant, water clear finish for use on

Hallmark TrueMark® Poly Finish and TrueMark® Glaze Tek Finish and NuOil® Finish. Mohawk Ultra™ Bond can also be used to repair small surface scratches on all Hallmark Floors wood flooring products. Ultra Bond™ adheres well to our wood finishes containing aluminum oxide as well as NuOil® two stage hybrid oil systems.



Blends well into the surrounding area providing a nearly invisible repair on surface scratches. A truly multi-purpose topcoat for those small repairs and finishing needs. Low odor and fast drying. When applying, wipe up overflow from area surrounding scratch with a clean tissue. Do not allow overflow to dry without removing. Remove excess Ultra Bond® immediately as the product completely dries within 2 to 3 minutes.

### Advantages:

- Easy to use.
- Excellent adhesion; blends well.
- Durable, resistant water clear finish.
- Multi-purpose topcoat for small repairs.

### Directions:

- Shake well before using.
- Test marker on a hidden area.
- To start flow press roller applicator down on floor surface and apply slight pressure to tube.
- Apply in even strokes.
- Wipe up overflow with tissue or finger. Leave no residue on surrounding finish.
- Multiple coats will produce better results.

Hallmark Floors Collections where Ultra Bond™ is Appropriate:



Ultra Bond™ market is in all kits and suitable for use on all Hallmark Floors finishes.

Safety cautions: WARNING! Causes eye and skin irritation. Harmful if inhaled. Vapor harmful. See Material Safety Data Sheet (MSDS) for complete information and First Aid. For industrial use only.

**KEEP OUT OF REACH OF CHILDREN!**

CONTAINS: Water, proprietary resin, glycol ether DPM, acrylic, isopropanol, propylene glycol.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products  
Division of RPM Wood Finishes Group, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Website: [www.mohawk-finishing.com](http://www.mohawk-finishing.com)



## 2. Mohawk Finishes - Pro Mark II & Ultra Mark Felt Tip Markers

Scratches that lightly penetrate the stain layer: Skill Level Basic

Product Description: The Pro-Mark II and Ultra Mark capillary markers feature excellent flow. Whether you need to touch-up 1 inch or 20 feet, the Pro-Mark II marker does it the first time and every time. The colors have excellent resistance to color fade, color shift from top coating and will not bleed. The nib offers superior flow along with the durability needed to do all normal repair work. The nib remains usable for the life of the marker. Marks equally well with the edge, the bottom or the tip. Good adhesion to most surfaces and resistance to polishes are built into the Pro-Mark II marker.

Markers will camouflage scratches that lightly reach into wood. Mark II and Ultra Mark felt tip markers contain both color and finish. Directions:

- Shake well before using.
- Test marker on a hidden area.
- To start flow press roller applicator down on floor surface and apply slight pressure to tip. To get color to the tip pump/press/depress the tip several times to draw color to end of tip.
- For scratches, stroke in direction of scratch.
- For worn areas, stroke in direction of wood grain.
- Apply in even strokes.
- Wipe up overflow with tissue or finger. Leave no residue on surrounding finish.
- Rub off excess colorant promptly with a soft cloth. Do not allow overflow to dry without removing. Remove excess Ultra Bond immediately as the product quickly dries completely.
- Multiple coats will produce better results.

To fill slight indentation above deeper scratch apply multiple coats (if necessary) use the Ultra Bond™ sponge tip marker on top of the repair to fill the void in the finish.

### Advantages:

- Fast and easy to use.
- Excellent flow. Will not skip even when used on porous materials.
- Good adhesion to most surfaces and resistance to polishes.
- Uniform color strength. Bleed resistant.
- Nib remains usable for the life of the marker for normal applications.

- Can be used at any angle, including upside down.
- Highest rated lightfast dyes for complete clarity and color retention.

Safety cautions: WARNING! Causes eye and skin irritation. Harmful if inhaled. Vapor harmful. See Material Safety Data Sheet (MSDS) for complete information and First Aid. For industrial use only.

KEEP OUT OF REACH OF CHILDREN!

Contains: alcohols, glycol ether DPM

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545

Website: [www.mohawk-finishing.com](http://www.mohawk-finishing.com)

## 3. Mohawk Finishes Fill Sticks / Moderate Scratches & Chips:

Skill Level Moderate



Mohawk Finishes Fill Stik™ can fill those moderate chips and scratches. Rub the stick into the scratch. It will fill with color and fill the scratch. Fill Stik is designed to camouflage the scratch. Deep heavy scratches may require a more advanced method of repair.

Product Description: The Mohawk Fil-Stik™ line is a semi-hard putty in stick form for the ultimate convenience offered to fill nicks, nail holes, cracks, etc. Can be protected with Tone Finish® aerosols or other coatings.

### Advantages:

- No heat or special tools required.
- Simply rub in and wipe off.
- Fade resistant, non-bleeding permanent colors.
- May be top coated immediately with Tone Finish® aerosols or other coatings.

### Directions:

- Surface should be clean and dry.

- Rub Fil-Stik™ into void.
- Press Fil-Stik™ into void with plastic leveling card or plastic putty knife.
- Draw plastic leveling card across filled area to level the fill.

Use caution when using plastic leveling card or plastic putty knife to avoid pulling Fil-Stik™ out of repair.

Carefully wipe off excess surrounding repair, using a cloth, May be protected with Ultra Bond Clear Finish Marker

NOTE: Components in Mohawk Touch Up Kit are compatible with:

- Hallmark XYZ refinishing system, for all TrueMark Poly & Glaze Tek finishes.
- Hallmark Restoration Oil, for all NuOil finishes

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545

Website: [www.mohawk-finishing.com](http://www.mohawk-finishing.com)



2360 S. Archibald Ave.  
Ontario, CA 91761

ff 888.551.0888

p 909.947.7736

f 909.947.7776

[www.hallmarkfloors.com](http://www.hallmarkfloors.com)

[info@hallmarkfloors.com](mailto:info@hallmarkfloors.com)