

# **TEST REPORT**

CLIENT	Hallmark Floors, Inc
--------	----------------------

	ASTM F2199 Standard Test Method for Determining Dimensional						sional		
TEST METHOD CONDUCTED	Stability	and	Curling	Properties	of	Resilient	Floor	Tile	after
	Exposure	to He	eat						



DESCRIPTION OF TEST SAMPLE				
IDENTIFICATION	Voyager PVC free polypropylene LVT			

## **GENERAL PRINCIPLE**

This test method is intended for use in determining the linear change of resilient flooring after being exposed to heat. The dimensional change over 12 inches is reported as the dimensional stability.

#### **TEST RESULTS**

Replicate	Identification		Result	Initial Curl	Final Curl
#1	Length	80°C	-0.002 Inch per 12 inches (0.02%)	0 Inch	0 Inch
	Width		-0.004 Inch per 12 inches (0.03%)		
#2	Length	80°C	-0.002 Inch per 12 inches (0.02%)	0 Inch	0 Inch
	Width		-0.004 Inch per 12 inches (0.03%)		
#3	Length	80°C	-0.002 Inch per 12 inches (0.02%)	0 Inch	0 Inch
	Width		-0.004 Inch per 12 inches (0.03%)		

APPROVED BY:

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical of similar products. This report, or the name of Professional Testing Laboratory Inc. shall not be used under any circumstance in advertising to the general public.

714 Glernwood Place Dalton, GA 30721 Phone: 706-226-3283 Fax: 706-226-6787 email: protest@optilink.us

Lan atluny



# **TEST REPORT**

CLIENT	Hallmark Floors, Inc	
--------	----------------------	--

	ASTM F2199 Standard Test Method for Determining Dimensional						sional		
TEST METHOD CONDUCTED	Stability	and	Curling	<b>Properties</b>	of	Resilient	Floor	Tile	after
	Exposure	to He	eat						



DESCRIPTION OF TEST SAMPLE				
IDENTIFICATION	Voyager PVC free polypropylene LVT			

## **GENERAL PRINCIPLE**

This test method is intended for use in determining the linear change of resilient flooring after being exposed to heat. The dimensional change over 12 inches is reported as the dimensional stability.

#### **TEST RESULTS**

Replicate	Identification		Result	Initial Curl	Final Curl
#1	Length	32°F	-0.003 Inch per 12 inches (0.03%)	0 Inch	0 Inch
	Width		-0.004 Inch per 12 inches (0.03%)		
#2	Length	32°F	-0.002 Inch per 12 inches (0.02%)	0 Inch	0 Inch
	Width		-0.004 Inch per 12 inches (0.03%)		
#3	Length	32°F	-0.004 Inch per 12 inches (0.03%)	0 Inch	0 Inch
	Width		-0.004 Inch per 12 inches (0.03%)		

APPROVED BY:

Lay athury

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical of similar products. This report, or the name of Professional Testing Laboratory Inc. shall not be used under any circumstance in advertising to the general public.

714 Glernwood Place Dalton, GA 30721 Phone: 706-226-3283 Fax: 706-226-6787 email: protest@optilink.us