



Arcadian Oak CCARC602MM



Ponderosa Pine CCPON6P2MM



Chaminade Oak CCCHA602MM



Provincial Oak CCPRO602MM



Chatham Walnut CCCHA6W2MM



Pumilla Elm CCPUM6E2MM



Cupari Acacia CCCUP6A2MM



Rubra Elm CCRUB6L2MM



Jari Oak CCJAR602MM



Sakonnet Oak CCSAK602MM



Morello Cherry CCMOR6C2MM



Senegalia Acacia CCSEN6A2MM



Chatham Walnut



Ponderosa Pine



Benefits

Finish:	Commercially Rated Wear Layer 100% Renewable w/Warranty intact Lifetime Finish Warranty
Structure:	Highest Achievable Stability 100% Quality Virign Vinyl Purecore Ultra - Lifetime Structure Guarantee
Clean Air:	Formaldehyde Free VOC free maintenance 100% Floor Score Certified

Features

Dimensions:	6" x 48" x 2mm
Wear Layer:	12mil (.3mm) Surface Guardian Basic
Surface Texture:	Wood grain embossing
Square Ft. per Box:	35.94
Weight per Box:	27.21
Planks per Box:	18
Usage:	Residential, Commercial
Edge Detail:	Square Edge
Warranty:	7 year commercial finish 25 year residential finish 10 year commercial structural Lifetime residential structural

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected *E1 Rating	EN 7171-1
Impact Insulation Class IIC	Eternity Underlayment IIC 71 Delta 21	ASTM E-492, E-989

ISO 14001 Certified Environmental Management System

2360 S. Archibald Ave.
Ontario, CA 91761
888.551.0888 t
909.947.7776 f
www.hallmarkfloors.com

