



**Granada Walnut** EDGRA6W3MM



**Valencia Teak** EDVAL6T3MM



**Seville Oak** EDSEV6O3MM



**Tortosa Sisal** EDTOR6S3MM



**Barcelona Spruce** EDBAR6S3MM



**Caceres Acacia** EDCAC6A3MM



**Cadiz Oak**



**Malaga Mahogany** EDMAL6M3MM



**Pyrenees Pine** EDPYR6P3MM



**Cadiz Oak** EDCAD6O3MM



**Madrid Maple** EDMAD6M3MM



**Barcelona Spruce**



**Cortez Oak** EDCOR6O3MM



**Gibraltar Oak** EDGIB6O3MM



## Benefits

Finish:	Anti Bacterial & Fungal Control Commercially Rated Wear Layer 100% Renewable with Warranty Intact Lifetime Finish Warranty
Structure:	Highest Achievable Stability Purecore Ultra - Lifetime Structure Warranty
Clean Air:	Formaldehyde Free VOC free maintenance 100% Floor Score Certified

## Features

Dimensions:	6" x 48" x 3mm
Wear Layer:	20mil (.5mm) Surface Guardian Pro®
Surface Texture:	Wood grain embossing depending on species
Square Ft. per Box:	24
Weight per Box:	28.66 lbs.
Planks per Box:	12
Usage:	Residential, Commercial
Edge Detail:	Beveled Edge
Warranty:	Lifetime Residential finish Lifetime Residential structural 10 year commercial finish 20 year commercial structural

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected *E1 Rating	EN 7171-1
Impact Insulation Class IIC	Eternity Underlayment IIC 71 Delta 21	ASTM E-492, E-989

ISO 14001 Certified Environmental Management System

Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring.  
Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3  
LEED: 25% recycled content contributing to MR credit 4.



2360 S. Archibald Ave.  
Ontario, CA 91764  
888.551.0888 t  
909.947.7776 f  
www.hallmarkfloors.com

