



Acadia Hickory
MS6ACAH



Sagamore Oak
MS6SAGO



Camden Maple
MS6CAMM



Seal Cove Hickory
MS6SEAH



Camden Maple



Mohegan Oak
MS6MOHO



Silver Creek Oak
MS6SILO



Montauk Maple
MS6MONM



Stony Brook Maple
MS6STOM



Silver Creek Oak



Oyster Bay Maple
MS6OYSM



White Plain Maple
MS6WHIM



moderno

Benefits

Finish	GlazeTek - 10x more durable than UV Oil 3x more durable than UV Poly 100% Renewable w/Warranty intact
Structure	MG4 - 3 Guaranteed sanding's Highest possible stability w/ Solid Dry Sawn faces Guaranteed Third Party Certification Truecore - FSC certified Highest Green Certification Lifetime Structural Guarantee
Clean Air	CARB II - Surpasses standard by over 50%

Features

Length:	Walnut & Hickory random up to 6' or 7' Oak is random up to 6'
Width:	6"
Thickness:	9/16" thick 4 mm sawn-cut face Truecore Centerply
Surface Texture:	Smooth
Finish:	Truemark Glaze Tek
Usage:	Residential, EN31, EN32
Edge Detail:	Microbevel
Warranty:	Lifetime Residential finish Lifetime Residential structural 5 year commercial finish 10 year commercial structural



V3 - MODERATE BOARD VARIATION



Color, Graining & Natural Changes

Wood is a natural product that features distinct color and graining. Each board is unique in its characteristics and will vary from piece to piece. The floor represents the natural characteristics of wood. Each board can vary from a clean to rustic visual and contain large to small filled knots, sap wood, small to large filled splits and a high contrast within the natural and lighter stained visuals. These subtleties may become more distinct over time due to exposure to direct sunlight. Occasional rearranging of furniture and rugs will help reduce the potential affects of the sun.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to www.hallmarkfloors.com to see our online room scenes and project galleries.

Maintenance

See Maintenance and Warranty Guide
Carb II Compliant

Installation



Nail Down



Glue Down



Float



Over Radiant Heat

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions. Hallmark Hardwoods Hickory Products are not approved for installation over Radiant Heat applications.

Trim Options

- Stair Nose Reducer
- T-molding Quarter Round
- Threshold