



Saffron Red Oak  
SOR34SAFR



Masala Oak  
SOR34MASO



Caraway Oak  
SOR34CARO



Moroccan Hickory  
SOR34MORH



Clove Hickory  
SOR34CLOH



Noni Oak  
SOR34NONO



Tulsi Hickory  
SOR34TULH



Cassia Maple  
SOR34CASM



Cardamom Maple  
SOR34CARM



Tamarind Walnut  
SOR34TAMW



Cassia Maple



## Benefits

Finish	NuOil – No recoat at time of install Best stain protection & color retention Completely VOC free 100% Renewable w/Warranty intact Custom 10 step reclaimed proprietary process
Structure	Solid Dry Sawn faces Guaranteed Third Party Certification
Clean Air	CARB II - Surpasses standard by over 50%

## Features

Length:	Random Length
Width:	3 1/4 & 4"
Thickness:	3/4" (Solid)
Surface Texture:	Rough Sawn, Wire brushed & Aged
Finish:	NuOil®
Usage:	Residential, EN31, EN32
Edge Detail:	Handcrafted Bevel
Warranty:	Lifetime Residential finish Lifetime Residential structural  3 year commercial finish 10 year commercial structural

Refer to [www.hallmarkfloors.com](http://www.hallmarkfloors.com) for latest, updated information.

## Color, Graining & Natural Changes

Organic 567 and Organic Solid wood floors are a natural product that feature distinct color and graining. The contrast of this collection can vary from light to dark visuals between boards along with the grading of large to small knots. Each board is unique in its characteristics and will vary from piece to piece. Each board contains large to small knots, heavy to light saw marks, sticker marks, over wood, face undulations, sap wood, small to large splits, and a high contrast within the natural and lighter stained visuals. Knots and voids may or may not be filled with dark putty.

The plank faces are naturally aged/fumed then wire brushed as a part of our 10 step proprietary process, creating a look that represents a true rustic visual with a possible high contrast between each board. These characteristics may become more distinct over time due to exposure to direct sunlight. Occasional rearranging of furniture and rugs will help reduce the potential effects of the sun.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to [www.hallmarkfloors.com](http://www.hallmarkfloors.com) to see our online room scenes and project galleries.

## Maintenance

See Maintenance and Warranty Guide  
Carb II Compliant

## Installation



Nail Down



Glue Down

Installs over: concrete and wood. Above, on or below grade. See complete installation instructions. Hallmark Solid Products are NOT approved for installation over Radiant Heat applications.

## Trim Options

- Stair Nose
- Reducer
- T-molding
- Threshold

