



Bridle Hickory SMBRI7H3MM



Piedmont French Oak SMPIE7O3MM



La Palma French Oak SMLAP7O3MM



Rawhide Hickory SMRAW7H3MM



Montecito French Oak SMMON7O3MM



Redondo French Oak SMRED7O3MM



Terret Walnut SMTER7W3MM



Riata Hickory SMRIA7H3MM



Oceanside French Oak SMOCE7O3MM



Solana French Oak SMSOL7O3MM



Pelham Maple SMPEL7M3MM



Newport Beach French Oak
SMNEW7O3MM



Oceanside French Oak



Redondo French Oak



Benefits

- Finish: Anit Bacterial & Fungal Control
Commercially Rated Wear Layer
100% Renewable with Warranty Intact
Lifetime Finish Warranty
- Structure: Highest Achievable Stability
100% Quality Virgin Vinyl
Purecore Ultra - Lifetime Structure Guarantee
- Clean Air: Formaldehyde Free
VOC free maintenance
100% Floor Score Certified

Features

- Dimensions: 7 1/4" x 48" x 3mm
- Wear Layer: 20mil (.5mm) Surface Guardian Pro®
- Surface Texture: Wood grain embossing
- Square Ft. per Box: 38.65
- Weight per Box: 41.8
- Planks per Box: 16
- Usage: Residential, Commercial
- Edge Detail: Square Edge
- Warranty: 10 year commercial finish
Lifetime residential finish
20 year commercial structural
Lifetime residential structural

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected *E1 Rating	EN 7171-1
Impact Insulation Class IIC	Eternity Underlayment IIC 71 Delta 21	ASTM E-492, E-989

ISO 14001 Certified Environmental Management System

2360 S. Archibald Ave.
Ontario, CA 91761
888.551.0888 t
909.947.7776 f
www.hallmarkfloors.com

