






Appaloosa Red Oak




Casita Hickory MY468CASH



Gaucho Hickory MY468GAUH



Puebla Hickory MY468PUEH



Ranchero Hickory MY468RANH



Calgary Red Oak MY468CGRO



Palomino Hickory MY468PALH



Villa Oak MY468VILO



Cheyenne Oak MY468CHEO




Alhambra Oak MY468ALHO



Appaloosa Red Oak MY468APRO



Adobe Red Oak MY468ADRO



Cantina Red Oak MY468CARO



Wharf Oak

Features

Length:	Up to 6' RL
Width:	4, 6 & 8" Random Width
Thickness:	1/2" Engineered 2mm Slice Cut Face
Finish:	TrueMark® Glaze Tek Poly
Edge Detail:	Handcrafted Microbevel
Certified:	TSCA Title VI Compliant 3rd Party Certified - Responsibly Harvested
TrueCore:	Third Party Certified veneer
Warranty:	Limited Lifetime residential finish Limited Lifetime residential structural 5 year commercial finish 10 year commercial structural
Maintenance:	Clean with TrueClean® Floor Cleaner. For full care and maintenance instructions visit HallmarkFloors.com/Floor-Care-Maintenance

Benefits

Finish:	12 coats of Aluminum Oxide hand glazed satin finish Guaranteed quality and durability - long lasting finish 100% renewable without sanding via a Screen & Recoat
Wear Layer:	Same visuals as 3/4" solid wood floors Top layer provides lasting durability Vertically sliced - Delivers greater strength
Structure:	Greater dimensional stability than 3/4" solid Healthy indoor air quality



Adobe Red Oak

Trim Options

Stair Nose
T-molding
Threshold
Reducer

Installation



Nail Down



Glue Down



Float



Over Radiant Heat
(Excluding Hickory)

Installs over: concrete, wood, vinyl floors and radiant heat systems. Above, on or below grade. See complete installation instructions. Hallmark Hickory and Solid products are not approved for installation over Radiant Heat.

Wood Characteristics

Color, Graining & Natural Changes



Wood flooring is a natural product that will feature distinct color and graining between planks. Each board contains large to small knots, sap wood, and a high contrast within the natural and lighter stained visuals. Knots and voids may or may not be filled with dark putty.

Note: This sample may not be representative of your entire installed floor, for your reference and the latest updated information, please refer to hallmarkfloors.com to see our online room scenes and product galleries.

Light Characteristics

Wood Floor Plank with Natural Finish
Light* Exposure Over 48 Months

New Installation			
			
12 Months Later	24 Months Later	48 Months Later	*All band widths

Before installation review the samples with the floor and verify our beautiful one of a kind floor is what you are expecting.

Installation constitutes acceptance.