



**Broadway Duomo Stone** TS6BRODS



**Central Park Wood End Grain** TS6CENWE



**Rockefeller Duomo Stone** TS6ROCDSD



**Wall St. Lineal Concrete** TS18WALLC



**Madison Stone/Concrete** TS18MADSC



**Canal Lineal Concrete** TS18CANLC



**5th Ave Stone/Concrete** TS18FTHSC



**Delaney Fabric** TS18DELFA



**St. Mark's Wood End Grain** TS6STMWE



**Grand Central Fabric** TS18GRAFA



**Delaney Fabric**



**Madison Stone/Concrete**



**TIMES  
SQUARE**  
LUXURY VINYL

## Benefits

- Finish:** Anti Bacterial & Fungal Control  
Commercially Rated Wear Layer  
100% Renewable with Warranty Intact  
Lifetime Finish Warranty
- Structure:** Highest Achievable Stability  
100% Phthalate free recycled content  
Purcore Eco - Lifetime Structure Warranty
- Clean Air:** Formaldehyde Free  
VOC free maintenance  
100% Floor Score Certified

## Features

- Dimensions:** 6" x 48" x 3mm - Plank (Duomo Stone & Wood End Plank)  
18" x 36" x 3mm - Tile (Stone/Concrete, Lineal Concrete, & Fabric)
- Wear Layer:** 20mil (.5mm) Surface Guardian Pro®
- Surface Texture:** Various
- Square Ft. per Box:** 36 Plank (Duomo Stone & Wood End)  
36 Tile (Stone/Concrete, Lineal Concrete, & Fabric)
- Lbs. per Box:** 37.16 Plank (Duomo Stone & Wood End)  
38.13 Tile (Stone/Concrete, Lineal Concrete, & Fabric)
- Pieces per Box:** 18 Planks (Duomo Stone & Wood End)  
8 Tiles (Stone/Concrete, Lineal Concrete, & Fabric)
- Usage:** Residential, Commercial
- Edge Detail:** Beveled Edge (Duomo Stone & Wood End Plank)  
Square Edge (Stone/Concrete, Lineal Concrete, & Fabric)
- Warranty:** Lifetime Residential finish  
Lifetime Residential structural  
10 year commercial finish  
20 year commercial structural

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected *E1 Rating	EN 7171-1
Impact Insulation Class IIC	Eternity Underlayment IIC 71 Delta 21	ASTM E-492, E-989

ISO 14001 Certified Environmental Management System

Certified FloorScore: Independent 3rd Party IAQ verification system for low emitting flooring.

Approved as CHPS 01350 compliant and recognized in LEED EQ Credit 4.3

LEED: Recycled content contributing to MR credit 4.

2360 S. Archibald Ave.  
Ontario, CA 91764  
888.551.0888 t  
909.947.7776 f  
www.hallmarkfloors.com

