



Charleston Oak TCCHA602MM



Concord Oak TCCON602MM



Savannah Oak TCSAV602MM



Winchester Oak TCWIN602MM



Cambridge Walnut TCCAM6W2MM



Appalachian Pine TCAPP6B2MM



Lexington Pecan TCLEX6P2MM



Shenandoah Oak TCSHE602MM



Wellesley Oak TCWEL602MM



Allegheny Oak TCALL602MM



Springfield Birch TCSPR6B2MM



Smoky Mountain Pine TCSMO6P2MM



Plymouth Maple TCPLY6M2MM



Blue Ridge Fir TCBLU6F2MM



Portsmouth Oak TCPOR602MM



Cumberland Cedar TCCUM6C2MM



Smoky Mountain Pine



Plymouth Maple

Benefits

Finish:	Commercially Rated Wear Layer 100% Renewable with Warranty Intact Lifetime Finish Warranty
Structure:	Highest Achievable Stability Purecore Ultra-Lifetime Structure Guarantee
Clean Air:	Formaldehyde Free VOC free maintenance 100% Floor Score Certified

Features

Dimensions:	6" x 36" x 2mm
Wear Layer:	12mil (.3mm) Surface Guardian Basic®
Surface Texture:	Ticking
Square Ft. per Box:	35.94
Weight per Box:	28.63
Planks per Box:	24
Usage:	Residential, Light Commercial
Edge Detail:	Square Edge
Warranty:	5 year commercial finish 25 year residential finish 10 year commercial structural Lifetime residential structural

Flexibility	Pass	ASTM F137
Thickness Standard	Pass	ASTM F386
Resistance to Chemicals (5 min.)	Pass	ASTM F925 5
Resistance to Chemicals (24 hr.)	Pass	ASTM F925
Heat Stability by Color Change	Pass	ASTM F1514
Light Stability by Color Change	Pass	ASTM F1515
Dimensional Stability after exposure to heat	Pass	ASTM F219
Fire Resistance	Class C - Pass	ASTM E 648
Coefficient of Friction	Pass	ASTM D2047-04
Static Load	Pass	ASTM F970-07
Stain Resistance	Pass	ASTM F925
Short Term Indentation	Pass	ASTM F1914-98
Smoke Density	Pass	ASTM E662-09
Wear Resistance	High	ASTM F510-93
Formaldehyde Emission (air)	None Detected	EN 7171-1
Impact Insulation Class IIC	Eternity Underlayment IIC 71 Delta 21	ASTM E-492, E-989

ISO 14001 Certified Environmental Management System

2360 Archibald Ave.
Ontario, CA 91764
888.551.0888 t
909.947.7776 f
www.hallmarkfloors.com

